

IP-COM

G1008M


8-Port Gigabit Ethernet Switch

G1008M

8-Port Gigabit Ethernet Switch

Descriptions

G1008M is a high-performance 8-Port Gigabit Ethernet Switch designed by IP-COM for such high-speed cascading scenarios as small/medium-sized video surveillance and office network of SMEs. With mini steel housing, the switch is excellent in heat dissipation. Offering 8*10/100/1000 Mbps auto-negotiation ports, the switch speeds up the transmission rate by 10 times, facilitating the transmission of large files and thus effectively solving such issues as video latency and scene loss in HD video surveillance. G1008M is easy to install either on a desktop or on a wall, without further configuration thanks to the plug and play feature, which is your ideal choice to improve network performance.



Features

- Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab and IEEE 802.3x
- 8*10/100/1000 Mbps auto-negotiation RJ-45 ports
- Up to 16 Gbps backplane bandwidth and non-blocking wire-speed forwarding
- Power and port status LED indicators for fault detection
- All metal housing, desktop and wall mounting

USPs



All Gigabit

The switch provides 8 gigabit ports, 10 times faster, ensuring smooth transmission of large files and videos.




DC 5-12V Power Input

The switch supports the power input of DC 5-12V, suitable for centralized power supply or on-site monitoring power supply.



Wall Mounting, Plug and Play


The switch supports both desktop and wall mounting, supports plug and play, thus easy for you to use.



Steel Housing, Stable Operation

The switch has a tough housing made of high quality steel, which is designed for excellent heat dissipation, ensuring stable operation and prolonging its lifespan. It is a reliable choice for outdoor video surveillance.

Typical Scenario



Specifications

Hardware Specifications

| | |
|-------------------------|---|
| Product Model | G1008M |
| Network Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x |
| Port | 8*10/100/1000 Mbps RJ-45 ports |
| Transmission Media | Recommended: CAT5 UTP, CAT5e UTP or better |
| Forwarding Rate | 10 Mbps: 14880 pps; 100 Mbps: 148800 pps; 1000 Mbps: 1488000 pps |
| Power Supply | Input: AC: 100-240V; 50/60Hz DC: 5-12V |
| Dimension (L*W*H) | 140 mm*66.5 mm*25.3 mm |
| LED Indicator | 1*Power; 8*Link/Act |
| Backplane Bandwidth | 16 Gbps |
| MAC Address Table | 8 K |
| Total Power Consumption | Total: 3 W |
| Forwarding Mode | Store and Forward |
| Protocol | CDMA/CD |
| MAC Address Learning | Auto Learning and Updating |
| Temperature | Operating temperature: 0°C - 40°C Storage temperature: -40°C - 70°C |
| Humidity | Operating humidity: (10% - 90%) RH, non-condensing Storage humidity: (5% - 90%) RH, non-condensing |
| Certificate | CCC、FCC、CE、RoHS |
| Certificate | 1*8-Port Gigabit Ethernet Switch 1*Power Cable 1*Quick Installation Guide |

IP-COM
World Wide Wireless

IP-COM NETWORKS CO., LTD.

Tower E3, No.1001, Zhongshanyuan Road,
Nanshan District, Shenzhen, China. 518052
Service: info@ip-com.com.cn
Inquiry: marketing@ip-com.com.cn
Tel: +86-755-27653089

Specifications are subject to change without notice. Copyright ©2021 IP-COM Networks Co., Ltd. All Rights Reserved. IP-COM is the trademark of IP-COM Networks Co., Ltd. All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.